

## Mixer-Angle-Grinder E 130mm Typ 419 with loading device



### Description

- CE-conform execution
- massiv machine frame, lowest noise level
- easy cleaning
- machine feet adjustable
- main switch and electric control integrated in machine housing
- touch sensitive keyboard operation
- protection cover at the barrel outlet, electrically controlled
- brake unit for meat worm drive
- retarded approach of the meat worm, longer service life of the cutting set
- surface and hopper stainless steel

- ejecting device for meat worm and cutting unit, manually operated
- hardly noticeable temperature rise with the final product
- mixing unit with mixing-worm and paddle-mixing-shaft
- Durable drives for meat- and feeder-worm, stainless steel drive shafts seated in ball bearings, special seal on the drive shaft
- drive shaft stainless steel, seated in special seals and ball bearings
- worm housing, meat worm and cutting unit stainless steel
- feeder worm stainless steel
- Cutting system Unger
- Careful processing of the raw materials
- smallest quantities can be mixed

## Specifications

---

type code	419	
standard operating voltage	400 V / 50 Hz	
rated power	16 kW	19 kW
rated current	35A	40 A
obligatory pre-fusing at customer site	35 A gL	50 A gL
length of connection cable	4 m	
cutting set	Unger E 130	
hole plate diameter	130 mm	
rated power meat worm drive	9/15 kW	11/18 kW
rated power feeder worm and mixing shaft drive	0,75/1,1 kW	
throughput	56 kg/min	
capacity of hopper (with hopper attachment)	245 l	
weight	930 kg	

## Options

---

- loading device hydraulically operated
- pylon loading device
- Hopper electrically opening
- meat worm drive extra power
- cleaning plat-form
- preselecting mixing time

## Accessories

---

- Transport and cleaning buggy
- Sorting device, manually operated

20.11.2009

[www.kgwetter.de](http://www.kgwetter.de)