

## Mixer-Angle Grinder G 160mm Typ 422 with loading device



### Description

- CE-conform execution
- massiv machine frame, lowest noise level
- easy cleaning
- machine feet adjustable
- main switch and electric control integrated in machine housing
- touch sensitive keyboard operation
- protection cover at the barrel outlet, electrically controlled
- brake unit for meat worm drive
- retarded approach of the meat worm, longer service life of the cutting set
- surface and hopper stainless steel
- ejecting device for meat worm and cutting unit, manually operated
- meat worm and mixing shaft with few handles dismountable for cleaning
- hardly noticeable temperature rise with the final product
- mixing unit with mixing-worm and paddle-mixing-shaft
- Durable drives for meat- and feeder-worm, stainless steel drive shafts seated in ball bearings, special seal on the drive shaft
- drive shaft stainless steel, seated in special seals and ball bearings
- worm housing, meat worm and cutting unit stainless steel
- feeder worm stainless steel
- Cutting system Unger
- smallest quantities can be mixed

### Specifications

type code

421

standard operating voltage	400 V / 50 Hz
rated power	19 kW
rated current	40 A
obligatory pre-fusing at customer site	50 A gL
length of connection cable	4 m
cutting set	Unger G 160
hole plate diameter	160 mm
rated power meat worm drive	11/18 kW
rated power feeder worm and mixing shaft drive	0,75/1,1 kW
throughput	70 kg/min
capacity of hopper (with protective grating)	245 l
weight	940 kg

### **Options**

---

- loading device hydraulically operated
- pylon loading device
- Hopper electrically opening
- cleaning plat-form
- preselecting mixing time

### **Accessories**

---

- Transport and cleaning buggy
- Sorting device, manually operated
- Sorting device, pneumatically operated