

Mixer-Angle-Grinder G 160mm Typ 422 without loading device



Description

- CE-conform execution
- massiv machine frame, lowest noise level
- easy cleaning
- machine feet adjustable
- main switch and electric control integrated in machine housing
- touch sensitive keyboard operation
- protection cover at the barrel outlet, electrically controlled
- brake unit for meat worm drive
- Protecting grate for hopper, electrically controlled
- surface and hopper stainless steel
- ejecting device for meat worm and cutting unit, manually operated
- hardly noticeable temperature rise with the final product
- mixing unit with mixing-worm and paddle-mixing-shaft
- Durable drives for meat- and feeder-worm, stainless steel drive shafts seated in ball bearings, special seal on the drive shaft
- drive shaft stainless steel, seated in special seals and ball bearings
- worm housing, meat worm and cutting unit stainless steel
- feeder worm stainless steel
- Cutting system Unger
- Careful processing of the raw materials
- smallest quantities can be mixed

Specifications

type code

422

standard operating voltage	400 V / 50 Hz
rated power	19 kW
rated current	40 A
obligatory pre-fusing at customer site	50 A gL
length of connection cable	4 m
cutting set	Unger G 160
hole plate diameter	160 mm
rated power meat worm drive	11/18 kW
rated power feeder worm and mixing shaft drive	0,75/1,1 kW
throughput	70 kg/min
capacity of hopper (with protective grating)	120 l
weight	910 kg

Options

- preselecting mixing time

Accessories

- Transport and cleaning buggy
- Sorting device, manually operated
- Sorting device, pneumatically operated