

Mixer-Automatic-Grinder E 130mm Typ 417



Description

- CE-conform execution
- massiv machine frame, lowest noise level
- easy cleaning
- machine feet adjustable
- main switch and electric control integrated in machine housing
- touch sensitive keyboard operation
- protection cover at the barrel outlet, electrically controlled
- brake unit for meat worm drive
- Protecting grate for hopper, electrically controlled
- retarded approach of the meat worm, longer service life of the cutting set
- surface and hopper stainless steel
- ejecting device for meat worm and cutting unit, manually operated
- meat worm, mixing shaft and feeder worm with few handles dismountable for cleaning
- hardly noticeable temperature rise with the final product
- mixing unit with mixing-worm and paddle-mixing-shaft
- Durable drives for meat- and feeder-worm, stainless steel drive shafts seated in ball bearings, special seal on the drive shaft
- drive shaft stainless steel, seated in special seals and ball bearings
- reverse run of the feeder worm during the mixing process
- worm housing, meat worm and cutting unit stainless steel
- feeder worm stainless steel
- Cutting system Unger
- Careful processing of the raw materials
- smallest quantities can be mixed

Specifications

type code	417
standard operating voltage	400 V / 50 Hz
rated power	9 kW
rated current	20 A
obligatory pre-fusing at customer site	25 A gL
length of connection cable	4 m
cutting set	Unger E 130
hole plate diameter	130 mm
rated power meat worm drive	6,8/8 kW
rated power feeder worm and mixing shaft drive	0,75/1,1 kW
throughput	45 kg/min
capacity of hopper	110 l
batch size for mixing process	60 kg
weight	590 kg

Options

- preselecting mixing time

Accessories

- Transport and cleaning buggy
- Sorting device, manually operated